

SOLOFOND

BASE REGULATOR



USED TO LEVEL THE BASE

Facilitates the application of the finishing render



PRODUCT INFORMATION

Consumption

100 g/m² of pure product (i.e. 200 g/m² of SOLOFOND diluted 1 for 1 by weight with water).

Colours

680 colours

Storage

18 months in its unopened original packing and stored away from freezing temperatures and heat.

Packaging

20 kg tub
5 kg tub

Supply

To obtain a consistent colour, it is recommended to only use products with the same batch number on a same facade, as the colour may vary depending on the manufacturing process.

SPECIFICATIONS AND PERFORMANCES

Appearance: white or coloured liquid

Composition: aqueous dispersion of acrylic resins, mineral fillers, additives

Density: 1.35

PERFORMANCE MEASURED AT +20°C

Adhesion to concrete and render	> 0.5 MPa
---------------------------------	-----------

FIELD OF USE

Purpose

Base coat for organic decorative "ribbed" finish renders and "ribbed" finish or "floated" finish thick mineral coatings.

Authorised bases

- Cast concrete.
- Lime-cement render or cement-based render.
- Single-layer render.
- Wall levelling.
- RHÉAMIX MONO [RHÉATHERM 600, RHÉATHERM 600 LR and RHÉATHERM 600 MOB ETICS systems].
- RHÉAPÂTE PE [RHÉA 400 ETICS system].

Unauthorised bases

- Horizontal or pitched outer parts at less than 45° from horizontal.
- Outer parts located less than 15 cm above ground level.
- Metal surfaces.

APPLICATION

Reference documents

Standard NF P 74-201 / DTU 59.1 of June 2013

Application conditions

- Application temperature: +5°C to +30°C.
- The base must not be frozen or overheated.
- Do not apply when rain or freezing temperatures are imminent

Precautions for use

In order to protect your health and the environment, and for the safe use of this product, follow the precautionary advice that is featured on the packing label.

You can find the safety instructions for this product on the Safety Data Sheet (SDS) available on quickfds.com.

Base preparation

- The base must be clean, healthy and free of any non-adhesive parts or areas that could prevent adhesion (for example: release oil, drying products, etc.).
- The base must be level. If necessary, level it with BÉTOMUR or PELLIPLAST wall levelling compound (see data sheets).
- Base with plant pollution (mosses, algae, lichens, fungi): Treat using an anticryptogamic solution.

Product preparation

- Mix SOLOFOND thoroughly in the tub before application.

- Before the LITHOCOLOR decorative render: Apply SOLOFOND pure.
- Before the "ribbed" appearance CRÉPILOR decorative render:
 - Dark colours: dilute SOLOFOND with water, 1 for 1 by weight.
 - Very light colours: apply SOLOFOND pure.

Application

WORKABLE TIME AT +20°C	
Drying time before covering	2 h

- Apply SOLOFOND (pure or diluted) in a single application using a brush or a lambs' wool roller to correctly impregnate the base.
- Clean the tools with water while the product is fresh.