

## VPI ENDUIT SEALER – Water based clear coating for all VPI Render Systems & porous masonry substrates



### PRODUCT DESCRIPTION

VPI Enduit Sealer is a water based protective coating that provides enhanced protection and water repellence to exterior or interior facades VPI Render systems and all other masonry substrates.

### PRODUCT PROPERTIES

- Enhanced weatherproofing for exposed locations
- Increased Algae and Mould resistance
- Provides Hydrophobic coating “lotus leaf effect”
- Maintains breathability of rendered facades
- Reduces the maintenance cycles of rendered facades

### SUITABLE SUBSTRATES

VPI Render Systems and porous materials including:

- MonoCal GM/GF
- RenoPass Heritage Range
- Rheatherm EWI Systems
- Crepilane TM/T & Crepilor TM/T
- Tradibatard/MonoCal Gris GF
- Brickwork/Blockwork/Stonework

### TECHNICAL CHARACTERISTICS

Water based liquid, chalky/milky in colour – Non Hazardous – Concentrate

### STORAGE

12 Month shelf life stored in a cool dry environment not in direct sunlight and at a consistent temperature. Product must not be exposed to direct sunlight and must be protected from heat. If subjected to frost, the product will become unfit for use.

### APPLICATION

VPI ENDUIT SEALER can be applied by rollers, by painting, flooding or airless spraying.

- THIS IS A CONCENTRATED PRODUCT
- Mix 2.5 Litres of ENDUIT SEALER with 22.5 Litres of clean tap water ensuring all concentrate is thoroughly mixed
- Surfaces must be clean and dry and free of all surface debris and loose material
- Apply using roller, brush or spray equipment applying a flood coat to all areas of the surface to be coated evenly.
- Leave to dry for 12-24 hours
- Repellence takes up to 48 hours to develop following application.

### APPLICATION CONDITIONS

- Temperature: +5°C - +30°C
- Do not apply in wet weather
- Do not apply if there is risk of frost/freezing conditions.

### HEALTH & SAFETY

Suitable protective clothing required when handling and using this product. The product is NON-Hazardous but can cause allergic reaction, irritation to eyes and harmful if consumed. Seek medical advice in case of contact with eyes. Keep out of the reach of children and minors. Always read and follow the guidance set out in the Health and Safety data sheet for this product.

### PACKAGING

2.5 Litres Drums – Sealed Lid – 58 Packs per pallet.

*Information provided in this document is based on our knowledge and experience of the products supplied, application results can vary depending on the application methods and skill of the installer of the products. Before application of the products in the information sheet it is recommended to check if this is the most up to date and current version of this document.*